



NOTES


1. Bolt-down capability is required on all frames, grates, and covers, unless specified otherwise in the Contract. Provide 2 holes in the frame that are vertically aligned with the grate or cover slots. The frame shall accept the 304 Stainless Steel (S.S.) 5/8" (in) - 11 NC x 2" (in) Allen head cap screw by being tapped, or other approved mechanism. Location of bolt-down holes varies by manufacturer.
2. All grates shall be 20" (in) x 24" (in).
3. Grate alternatives shown for informational purposes. Grate design varies by manufacturer and must meet ADA requirements.
4. Refer to **Standard Specification Section 9-05.15 and 9-05.15 (2)** for additional requirements.




**PLAN VIEW
GRATE FRAME**
FOR DETAILS NOT SHOWN,
SEE STANDARD PLAN B-30.10





**PLAN VIEW
GRATE
ALTERNATIVE 1**



**PLAN VIEW
GRATE
ALTERNATIVE 2**



**PLAN VIEW
GRATE
ALTERNATIVE 3**



**ISOMETRIC VIEWS
(GRATE ALTERNATIVE 1 SHOWN)**



**ADA GRATES FOR
RECTANGULAR FRAMES**
STANDARD PLAN B-30.15-00

SHEET 1 OF 1 SHEET

APPROVED FOR PUBLICATION

STATE DESIGN ENGINEER
Washington State Department of Transportation